

Fabric characteristics

	Standard	Solids & Textured
Composition		100% Solution-dyed acrylic fiber
Type of fabric		Special acrylic for upholstery
Finish		Special Infinity treatment for upholstery. Water repellent, stain resistant, rot-proof and breathable. PFAS Free
Use		Indoor & Outdoor

Technical characteristics

Weight	ASTM D3776	7.9 oz/yd ²
Width	ASTM D3774	55"
Standard roll length	ASTM D3774-18	65.6 yards
Water column	AATCC TM 127	24,5 mbar
Spray test	AATCC 22	100
Tensile strength (warp)	ASTM D5034	317 lbf
Tensile strength (weft)	ASTM D5034	162 lbf
Tear strength (warp)	ASTM D2261	20.0 lbf
Tear strength (weft)	ASTM D2261	12.9 lbf
Color fastness to artificial light Xenotest (Indoor)	UNE-EN ISO 105 B02:2014	4-5
Color fastness to artificial light (Outdoor)	UNE-EN ISO 105 B04:1998	7-8
Wyzenbeek abrasion	ASTM D4157	40.000 cycles
UV Standard 801	UV Standard 801	Pass
Antimicrobial activity	AATTCC Test Method 100-2012	Up to 99,99% bacteria growth reduction
California Technical bulletin #117	TB 117-2013	Pass
UFAC Flammability	UFAC Flammability	Class I
Cleaning instructions		

Specifications and colors may change slightly over time, and for the most thorough and up to date technical information, please refer to our web site

Safety, health and environment



PFAS free



Phthalates Free



Recyclable



Made in Europe



5 Years warranty



SENS V1/06/24



STANDARD 100
2011OK0127
AITEX
www.oeko-tex.com



RECASENS
BCN 1886